


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

Index File No. E-17

**History of original corner establishment:**

Corner was originally established by Rufus S. Moore under GLO contract No. 451 during November, 1882. Surveyor General's notes state: "Set a basalt stone 18x8x7 ins., 12 ins. in the ground for cor. to cecs. 2,3, 10, and 11. marked with 5 notches on S and 2 notches on E edges. From which: A fir 34 ins. diam. bears N30°E, 20 lks. dist. marked T3SR34ES2 BT. A fir 42 ins. diam. bears N48°W, 57 lks. dist. marked T3SR34ES3 BT. A fir 34 ins. dia. bears S18°W, 43 lks. dist marked. T3SR34ES10 BT. A fir 14 ins. diam. bears S 48°E, 33 lks. dist marked T3SR34ES11 BT."




**Description of corner evidence found:**

Found 19x9x8 inch ctone loosely set in ground with 5 and 2 notches. From which: A 36" rotten stump bears N25°E, 14.2 ft. scribed. A down and rotten 16" fir bears S48°E, 22.0 ft. with full scribe. A rotten lig bears approximately S70°W, 30 ft. and a 42" rotten stump bears N49°W, 39.7 ft.

**Description of monument and accessories | established to perpetuate the original location of this corner:**

At center of the above stone set 2 1/2" X 30 " galvanized pipe and brass cap marked: Set pipe 24" in the ground and mound of stone around to cap. Placed marked stone alongside. From whch by magnetic declination of N20°E: A 12" fir bears N69°E, 25.4 ft. scribed T3SR34ES2 BT. A 12" fir bears S40°E, 30.4 ft. scribed T3SR34ES11 BT. A 20" pine bears S 82°W, 23.6 ft. scribed T3SR34ES10 BT. A 10" fir bears N63°W, 24.4 ft. scribed T3SR34ES3 BT. Painted blazes red and 6" red band around. placed 54-3s, 54-4s and brass washers stamped PLS 1051 on BT. Placed 54-4 on steel fence post 5' north of the corner.



I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel Rowland  
Steve Campbell

September 19, 1980

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Barry B. Barbour*

OREGON  
EST. 17, 1975  
BARRY B. BARBOUR  
1 0 5 1

Office of... County... Surveyor..... County of... Union.....  
State of... Oregon....., I hereby certify that the within instrument was filed in this office  
for record on the... 30th day of... January....., 19... 81

..... by .....  
(COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY  
SURVEYOR**

---

Date Received PO-788-276

Date Filed \_\_\_\_\_

By \_\_\_\_\_

File No. 375-84R