## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. E-19

## History of original corner establishment:

Corner was originally established by Rufus S. Moore, under GLO contract No. 451, during November, 1882. Surveyor General's notes state: "Set a post 3 ft, long, 3 ins. sq. 24 ins. in the fround for 1/4 sec. cor. marked 1/4 S on N. face, from which: A pine 40 ins. in dia. bears S35°W, 19 lks. dist. marked 1/4 S BT. A pine 3 ins. in dia. bears N1°W, 13 lks. dist. marked 1/4 S BT."

DIAGRAM T3S R34E S2 S11

## Description of corner evidence found:

Corner falls on a flat bench in thick lodgepole pine. Several hours were spent searching for the corner. No large pines were found in the area of the corner. Every large pine within 300 ft. of the corner was checked with no results.

## Description of monument and accessories I established to perpetuate the original location of this corner:

T3S R34E After a diligent search, at the surveyed point set 2 1/2" X S2 30" galvanized pipe and brass cap marked: Set pipe 25" in the gound and small mound of stone around to cap. S11 From which by magnetic declination of N20°E: A 9" lodgepole pine bears S77°E, 75.0 ft. scribed

1980

1/4 S11 BT. An 8" fir bears N23°W, 28.2 ft. scribed

1/4 S2 BT. Painted blazes red and 6" red band around. Placed 54-3s, 54-4s, OR PLS 1051 and brass washers stamped PLS 1051 on the BTs. Placed 54-4 on a steel fence post 5' west of the corner.

REGISTERED PROFESSIONAL LAND SURVEYOR OREGON OCT. 17, 1975 BARRY B. BARBOUR

1051

I hereby certify that the above corner monument was reestablished as herein described.

File No. 376-84 R

Witnesses: Daniel Rowland Harlan Eden

October 9, 1980

Office of County Surveyor	County of Union	
State of Oregon / hereby certify the	hat the within instrument was filed in this off	ice
for record on the 30th. day ofJanuary		UMION COUNTY
(COUNTY OFFICIAL)	(DEPUTY)	JORVETOR
Form R6-7100-57 (9/71)		Date Received
Form R6-7100-57 (9/71)		