


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. G-21

History of original corner establishment:

Corner was originally established by Rufus S. Moore under GLO contract NO.451 during November, 1882. Surveyor General's notes state: "Set a basalt stone 16x8x7 ins., 11 ins, in ground for 1/4 sec. cor marked 1/4 on W face. From which: A pine 30 ins. diam. bears N19°E, 47 lks. dist. marked 1/4S BT. A pine 16 ins. diam. bears S69°W, 20 lks. dist. marked 1/4S BT."




Description of corner evidence found:

Found 18x10x5 inch stone firmly set and marked 1/4 on west side from which a dead 24" pine bears N49°E, 32.2 ft. scribed 1/4S BT. A 24" pine bears S 67°W, 14.0 ft. live grown over blazes.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2 1/2" X 30" galvanized pipe and brass cap marked: Set pipe 22" in the ground and mound of stone around to cap. Placed marked stone alongside. From which by magnetic declination of N20°E: A 9" fir bears S42°E, 14.3 ft. scribed 1/4S BT. Placed 54-3s and 54-4s on old and new BTs. Painted balzes red and 6" red band around. Placed brass washers stamped PLS 1051 on BTs.



I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel Rowland
Steve Campbell

September 18, 1980

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Barry B. Barbour
**OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051**

Office of...County..Surveyor..... County of Union.....

State of...Oregon....., I hereby certify that the within instrument was filed in this office for record on the...30th day of...January....., 1981.

(COUNTY OFFICIAL)

(DEPUTY)

**UNION COUNTY
SURVEYOR**

Date Received

Date Filed

By

File No. 383-84 R