

T3534 J01

Remonumentation of Certain Original Corner Points  
T. 3 S., R. 33½ E., Willamette Meridian, Oregon

The cor. of secs. 7, 12, 13, and 18, determined at record bearing and distance from the remains of the original bearing trees:

A root hole, bears N. 35° E., 26 lks. dist., with a down and decayed western larch alongside, 12 ins. diam., with scribe marks BT visible on decayed blaze.

A decayed western larch snag, 24 ins. diam., bears S. 42° E., 16 lks. dist., with scribe marks S R34E S18 visible on decayed blaze.

A pine snag, 9 ins. diam., bears N. 19° W., 42 lks. dist., with scribe marks T3S R33½E S12 BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 3 S	
R 33½ E	R 34 E
S 12	S 7
S 13	S 18
1975	

from which new bearing trees

A fir, 17 ins. diam., bears N. 35½° E., 57 lks. dist., mkd. T3S R34E S7 BT.

A western larch, 18 ins. diam., bears S. 42½° E., 63 lks. dist., mkd. T3S R34E S18 BT.

A fir, 12 ins. diam., bears S. 55½° W., 35½ lks. dist., mkd. T3S R33½E S13 BT.

A fir, 10 ins. diam., bears N. 15½° W., 18 lks. dist., mkd. T3S R33½E S12 BT.

Subdivision, T. 3 S., R. 33½ E.,  
Willamette Meridian, Oregon

(Remonumenting corners established by  
Rufus S. Moore, Deputy Surveyor, in 1882)

The ¼ sec. cor. of secs. 25 and 26, monumented with a basalt stone, 12 x 8 x 6 ins., loosely set 2 ins. in the ground, no marks visible, from which the remains of the original bearing trees:

A fir snag, 12 ins. diam., bears East, 3 lks. dist., with healed blaze.

A western larch snag, 7 ins. diam., bears N. 70° W., 8 lks. dist., with scribe marks S visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T3534 J01

T3532 1/2 T21

UNION COUNTY  
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By [Signature] DEPUTY

File No. 374-2013R