


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

In 1882, under GLO Contract No. 451, Rufus S. Moore set a post, from which a 5" Pine bears S50°W, 9 lks. and a 4" Pine bears S79°E, 16 lks

Index File No. P-25




Description of corner evidence found:

Found BLM 3 1/4" brass cap on 2 1/2" iron pipe rising 8", stamped:

Bearing trees found:

An 18" D. Fir bears S67°E, 56.3 ft., scribing visible
An 8" dead & down L. Pine bears S50°W 9 lks., scribing visible "1/4 S BT".



Description of monument and accessories established to perpetuate the original location of this corner:

New BT's:

A 6" W. Larch bears S63°W, 11.9 ft., scribed 1/4 S24 BT.

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982.

Compass Declination: 19 1/2°E

Witness: G. Arrand

From 2115, south on 2115-050 1/4 mi. A little pine on the right up the bank has a yellow tag saying go 800 ft. up the hill to the top. The corner is 75 ft. into the woods.

I hereby certify the above described corner monument and/or accessories was established as described on June 6, 1984



Office of..... County of.....

State of..... I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY
SURVEYOR**

Date Received 7-2-84

☆ GPO-798-276

Date Filed 7-3-84

By G. LANGLITZ, DEPUTY

File No. 890-84 R

T3S34P01

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 33½ E., Willamette Meridian, Oregon

CHAINS

Deposit corner stone alongside iron post.

The ¼ sec. cor. of secs. 19 and 24, determined at record bearing and distance from the remains of the original bearing trees:

A pine, 8 ins. diam., bears S. 50° W., 9 lks. dist., with scribe marks ¼ S BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 3 S
¼
R 33½ E | R 34 E
S 24 | S 19
1975

from which a new bearing tree

A fir, 15 ins. diam., bears S. 67° E., 86 lks. dist., mkd. ¼ S19 BT.

The cor. of secs. 13, 18, 19, and 24, determined at record bearing and distance from the remains of the original bearing trees:

A decayed pine stump, 12 ins. diam., bears N. 19° E., 210 lks. dist., with scribe marks T3S R34E S18 visible on open blaze.

A root hole, bears N. 59° W., 53 lks. dist., with a down and decayed pine alongside, 12 ins. diam., with scribe marks T3S R33½E S13 visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, to solid rock, in a mound of stone, 4½ ft. base, to top, with brass cap mkd.

T 3 S
R 33½ E | R 34 E
S 13 | S 18
S 24 | S 19
1975

from which new bearing trees

A pine, 10 ins. diam., bears N. ½° E., 105 lks. dist., mkd. T3S R34E S18 BT.

A pine, 12 ins. diam., bears S. 28° E., 162 lks. dist., mkd. T3S R34E S19 BT.

A pine, 8 ins. diam., bears S. 84° W., 79 lks. dist., mkd. T3S R33½E S24 BT.

A pine, 10 ins. diam., bears N. 67½° W., 34 lks. dist., mkd. T3S R33½E S13 BT.

T3S34P01

T3S34 N01

UNION COUNTY
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By J. G. L. DEPUTY

File No. 376-2013R