


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. X-05

History of original corner establishment:

In 1882, under GLO Contract No. 451, Rufus S. Moore set a stone 15x12x4, from which a 12" Fir bears N53°W, 12 lks. and a 20" Fir bears S78°E, 17 lks.



Description of corner evidence found:

No corner monument found.

Bearing trees found:

- A 24 1/2" Fir bears N53°W, 7.9 ft., blaze healed.
- A 23" Fir bears S78°E, 11.2 ft., blaze healed.

Description of monument and accessories established to perpetuate the original location of this corner:

Set 2 1/2"x30" aluminum capped aluminum pipe rising 7", stamped:

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982.

T3S R34E
 1/4
 S31-S32
 RLS 1848
 1984

Compass Declination: 19 1/2°E
Witness: G. Arrand

Set metal fence post 5 ft. north of corner.

From 2110-146, take 2100-140 northeasterly .7 mi. to where road hooks around the ridgetop and goes south. Follow ridge top north to the end of the clearing (about .2 mi.). Corner is east 800 ft. down steep slope. 120 ft. west of Cougar Creek.

I hereby certify the above described corner monument and/or accessories was established as described on June 8, 1984

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

B. A. Sutton

OREGON
 JULY 13, 1979
 B. A. SUTTON
 1848

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY
 SURVEYOR**

Date Received 7-2-84

Date Filed 7-3-84
☆ GPO-798-276

By G. LANGLITZ DEPUTY

File No. 910-84 R