


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. Z-25

History of original corner establishment:

In 1882, under GLO Contract No. 451, Rufus S. Moore set a stone 16x10x6, no bearing trees set.



Description of corner evidence found:

Only corner evidence found was an unrecorded bearing tree:
A 14" L. Pine snag 5 ft. high, bearing S59°W, 11.0 ft., meas. dist. & bear. scribing visible "T4S R33 1/2E BT"


The new corner was set at the single proportioned location and the unrecorded bearing was located from that corner by bearing and distance.

Description of monument and accessories | established to perpetuate the original location of this corner:

Buried a 2 1/2" x 30" aluminum capped aluminum pipe 6" below surface of road in south tire track, westerly, cap stamped:

New BT's:

- A 6" W. Larch bears N19 3/4°W, 45.7 ft., scribed T3S R33 1/2E S36 SC BT.
- A 4.5" R. Fir bears N50°E, 24.7 ft., scribed "X" BT.



1984
RLS 1848

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March, 1982. Set metal fence post 16 ft. north and 10 ft. west of corner.

Compass Declination: 19 1/2°E

Witness: G. Arrand

From 21, take 2100-102 westerly & northerly .3 mi. to cable gate. Corner is 20 ft. ahead in left tire track.

I hereby certify the above described corner monument and/or accessories was established as described on May 16, 1984.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

OREGON
JULY 13, 1979
B. A. SUTTON
1848

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY
SURVEYOR**

Date Received 7-2-84

☆ GPO-798-276

Date Filed 7-3-84

By G. LANGLITZ, DEPUTY

File No. 907-84R