


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. Z-03

History of original corner establishment:

In 1882, under GLO Contract Co. 451, Rufus S. Moore set a post, from which a 7" Pine bears N38°W, 23 lks. and a 30" Fir bears S5°W, 9 lks.



Description of corner evidence found:

Bearing Trees Found:

A 38" W. Fir bearing S5°W, 7.0 ft. to center of tree. Blaze visible.  
A 7" Pine bearing N38°W, 15.2 ft., original BT.

Description of monument and accessories established to perpetuate the original location of this corner:

Set 2 1/2"x30" aluminum capped aluminum pipe, stamped: rising 18" in mound of stones.

New BT's:

A 6" W. Fir bearing N4 1/2°W, 21.0 ft., scribed "1/4 S31 BT"  
An 8" W. Fir bearing N79°E, 59.5 ft., scribed "1/4 S31 BT".

T3S	R34E
	SC
	1/4
	<u>S31</u>
	T4S
	1984
RLS	1848

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March, 1982. Set metal post 6 ft. north of corner.

Compass Declination: 19 1/2°E  
Witness: G. Arrand

From 2100-146, take 2100-147 north 1/8 mi. Follow the ridge north 200 ft. Veer to the northwest. Corner is in bottom of draw.

I hereby certify the above described corner monument and/or accessories was established as described on May 14, 1984.

REGISTERED PROFESSIONAL LAND SURVEYOR
<i>B. A. Sutton</i>
OREGON JULY 13, 1979 B. A. SUTTON 1848

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by .....  
(COUNTY OFFICIAL) (DEPUTY)

<b>UNION COUNTY SURVEYOR</b>
Date Received <u>7-2-84</u>
Date Filed <sup>☆ GPO-7827</sup> <u>7-3-84</u>
By <u>G. LANGLITZ, DEPUTY</u>
File No. <u>911-84 R</u>