


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. Z-05

History of original corner establishment:

In 1882, under GLO Contract No. 451, Rufus S. Moore set a post, from which an 8" Sugar Pine bears N68°W, 30 lks. and a 12" Pine bears N8°E, 16 lks.



Description of corner evidence found:


Bearing Trees Found:

- A 14" Spruce bearing N68°W, 19.8 ft., blaze visible.
- A dead standing W. Larch bearing S57°W, 18.8 ft., blaze & scribing visible. Unrecorded BT.

Description of monument and accessories established to perpetuate the original location of this corner:

New BT's:

- A 7" Spruce bearing N60°W, 47.2 ft., scribed "T3S R34E S31 BT".
- A 5" Spruce bearing N57 1/2°E, 23.2 ft., scribed "T3S R34E S32 BT".



Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March, 1982. Set metal post 5 ft. north of corner.

Compass Declination: 19 1/2°E

Witness: G. Arrand

From 2105-149, take 2105-142 approx. 1.1 mi. to the end. Corner is about 200 ft. N20°W in a little draw coming from the west down into Cougar Canyon.

I hereby certify the above described corner monument and/pr accessories was established as described on May 14, 1984.

**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

*B. A. Sutton*

OREGON  
JULY 13, 1970  
B. A. SUTTON  
1848

Office of..... County of.....

State of..... I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by .....  
(COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY  
SURVEYOR**

Date Received 7-2-84

Date Filed <sup>GPO-798-276</sup> 7-3-84

By G. LANGRISH, DEPUTY

File No. 912-84R