


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. Z-09

History of original corner establishment:

In 1882, under GLO Contract No. 451, Rufus S. Moore set a stone 14x10x7, from which a 7" Pine bears N62°W, 34 lks. and a 45" Pine bears N63°E, 32 lks.



Description of corner evidence found:

Found original stone with notches.

Bearing Trees Found:

- A 18.5" P. Pine bearing N62°W, 22.9 ft., blaze healed.
- A 35" stump with toe of blaze bearing N63°E, 21.3 ft. to face of blaze.

Description of monument and accessories established to perpetuate the original location of this corner:

Set 2 1/2"x30" aluminum capped aluminum pipe, rising 14" in mound of stones. Original stone set on north side of ACAP in mound of stones.

New BT's:

- A 5" P. Pine bearing N28°E, 44.3 ft., scribed "T3S R34E S33 BT".

stamped:

T3S R34E
 SC
S32 | S33
 T4S
 1984
 RLS 1848

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982.

Compass Declination: 19 1/2°E
Witness: G. Arrand

From 2105-135, go north 1/2 mi. on 2105-101 to the fence line. Follow the fence line east 500 ft. to corner.

I hereby certify the above described corner monument and/or accessories was established as described on May 16, 1984.



Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....
 by
 (COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR	
Date Received	<u>7-2-84</u>
Date Filed	<u>7-3-84</u>
By	<u>G. LANGRISH DEPUTY</u>
File No.	<u>914-84R</u>