

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


History of original corner establishment:

Original corner established in 1882 by Rufus Moore.

Set a basalt stone 18"x 11"x 11", 12" in ground for 1/4 sec. corner marked 1/4 on north face. From which:

A 18" Pine bears: N 63° W, 69 links. (45.5')

A 9" Pine bears: S 61° W, 43 links. (28.4')



Description of corner evidence found:

A stone mound was found at the correct bearing and distance under a down log, but no stone was found of the correct size.

A 19" Ponderosa Pine bears: N 64° W at 45.5 ' with visible scribing.

SEE SURVEY
35-86

UNION COUNTY SURVEYOR

Date Received 10-2-86

Date Filed 10-13-86

By G. LANGLITZ, DEPUTY

File No. 183-86 R


Description of monument and accessories established to perpetuate the original location of this corner:

Set a 2"x 30" galvanized iron pipe with 2 1/2" brass cap marked:

Pipe is set in ground 12" in a mound of stones.

New Bearing Trees:

An 8" Ponderosa Pine bears: S 32° 45' W, 20.6', scribed " 1/4 S B.T." on a single blaze. A 3/4" aluminum washer marked: " RLS 852" is nailed between the letters B and T.. The tree is painted with a 6" red band and has U.S.F.S. Bearing Tree and Land Survey Monument signs attached.



A steel fence post is set 5' from the brass cap with a U.S.F.S. Land Survey Monument sign attached.

I certify the above corner point was perpetuated hereon as described on July 15, 1986.

REGISTERED PROFESSIONAL LAND SURVEYOR

David L. Haddock
OREGON
JULY 12, 1988
DAVID L. HADDOCK
852

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....
..... by

(COUNTY OFFICIAL)

(DEPUTY)