


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner established by Rufus Moore in 1882.

Set a basalt stone 14" x 8" x 7", 10" in ground for corner to sections 34 and 35 marked with 2 notches on the east and 4 notches on the west edge and raised a mound of stones along side. From which:

- A 34" Pine bears: N37°E, 166 links.(109.6')
- A 7" Pine bears: N42°W, 137 links.(90.4')




Description of corner evidence found:

A stone with notches faintly visible on one side in a typical mound.

An old stump with faint axe marks visible bears: N37°E, 109.6' from the corner. No trace of the other bearing tree was found.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2" x 30" galvanized iron pipe with 2 1/2" brass cap marked: Pipe is set in ground 6" in a mound of stones. Original stone is placed in stone mound along side of the pipe.



New Bearing Trees:

An 8" Ponderosa Pine bears: N52°00'W, 50.9' scribed: T3S R34E S34 BT in a double blaze. A 10" Ponderosa Pine bears: N40°00'E, 66.2' scribed: T3S R34E S35 BT in a double blaze. A 3/4" aluminum washer stamped RLS 852 is nailed between the letters B and T on each tree. Each tree is painted with a 6" red band and has USFS Bearing Tree and Land Survey Monument signs attached. A steel fence post is set 5' from the brass cap and has a USFS Land Survey Monument sign attached.

I hereby certify the above corner point was perpetuated as hereon described on July 15, 1986.

REGISTERED PROFESSIONAL LAND SURVEYOR

David L. Haddock

OREGON JULY 12, 1988 DAVID L. HADDOCK 852

Office of..... County of..... State of..... I hereby certify that the within instrument was filed in this office for record on the..... day of..... 19.....

(COUNTY OFFICIAL)

UNION COUNTY SURVEYOR

(DEPUTY)

Form R6-7100-57 (9/71)

Date Received 10-2-86
 Date Filed 10-13-86
 By G. LANGLITZ DEPUTY
 File No. 182-86 R

SEE SURVEY 35-86