


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner established in 1882 by Rufus Moore.

Set a basalt stone 12"x 11"x 5", 8" in ground for  $\frac{1}{4}$  sec. Corner marked  $\frac{1}{4}$  on north face and raised mound of stone along side. From which:

A 38" Pine bears: S 88° W, 291 links. (192.1')



Description of corner evidence found:

Stone 12"x 11"x 5" with  $\frac{1}{4}$  visible in stone mound.

A 40" Ponderosa Pine with visible scribing bears: S 88° W, 195.3'.

SEE SURVEY  
35-86

**UNION COUNTY SURVEYOR**

---

Date Received 10-2-86

Date Filed 10-13-86

By G. LANGLITZ, DEPUTY

File No. 181-86 R


Description of monument and accessories established to perpetuate the original location of this corner:

Set a 2"x 30" galvanized iron pipe with a 2 $\frac{1}{2}$ " brass cap marked:

Pipe is set 18" in ground in a mound of stones. Original stone is placed along side of pipe.

New Bearing Tree:

A 12" Ponderosa Pine bears: S 0° 45' E, 97.9' scribed " $\frac{1}{4}$  S B.T." on a single blaze. A  $\frac{3}{4}$ " aluminum washer marked: "RLS 852" is nailed between the letters B and T. The tree is painted with a 6" red band and has U.S.F.S. Bearing Tree and Land Survey Monument signs attached.



A steel fence post is set 5" from the brass cap with a U.S.F.S. Land Survey Monument sign attached.

I hereby certify the above corner point was perpetuated as hereon described on July 15, 1986.

**REGISTERED PROFESSIONAL LAND SURVEYOR**

*David L. Haddock*

**OREGON**  
JULY 12, 1968  
**DAVID L. HADDOCK**  
852

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by .....

(COUNTY OFFICIAL) (DEPUTY)