


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. ^A 8-19

History of original corner establishment:
 In 1882, Rufus S. Moore, under GLO Contract No. 451, set a 3 ft. long post 3 in. sq. 18 inches in the ground with mound of stone 3 ft. at the base and 18" high for 1/4 Sec. Cor.
 From which:

A leaning pine 26" dia. bears N82° E 141 lks. scribed "1/4 S BT".

A Pine 10" dia. bears S50°E 121 lks. scribed "1/4 S BT"



Description of corner evidence found:

FOUND: 30" Ponderosa Pine stump with "BT" scribing.

56" leaning Ponderosa Pine, no visible markings. At record bearing and distance from the two trees found scattered mound of stone.

Description of monument and accessories established to perpetuate the original location of this corner:

At the True Corner Point established by reference to the original bearing trees, we set a 2 1/2" x 30" galvanized pipe 14" in ground with mound of stone and dirt to cap, with 3" brass cap stamped:

From which:

A Ponderosa Pine 10" dia. bears N31°E 23.2 ft. scribed
 T2S R35E 1/4 S35 BT.

A Ponderosa Pine 7" dia. bears S51°E 13.8 ft. scribed
 T3S R35E 1/4 S 2 BT.

Attached 54-3 and 54-4 signs to both new BT's and old stumps. Painted blazes and 6" band around both BT's. Attached brass washer stamped "LS 1099" to foot blaze of both BT's. Attached 54-4 signs to metal fence post set 5 ft. east of monument.

Compass Declination: 18 1/2° East.

I hereby certify the above described corner monument and or accessories was established as described on June 18, 1981.

Witnesses: Glen Wagoner
 Millard Wyatt



Office of.....Surveyor..... County of..... Union.....
 State of.....Oregon....., I hereby certify that the within instrument was filed in this office
 for record on the...4... day of...OCTOBER....., 1982.....
Howard L. Perry..... by Gary L. Langlitz.....
 (COUNTY OFFICIAL) (DEPUTY)

<p>CLATSOP COUNTY DEPUTY SURVEYOR</p>
<p>and _____</p> <p>dated <u>★ GPO-700-276</u></p>
<p>By _____</p>
<p>File No. <u>399-84R</u></p>