CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: In 1882, Rufus S. Moore, under contract No. 451, set a post 4 1/2 ft. long and 5" square 2 feet in the ground for Cor. to Sec. 1, 2, 35, 36. From which:

A Pine 15" dia. bears S50°E 55 lks dist. scribed T3S R35E S1 BT.

A Tamarack 20" dia. bears N56°W 30 lks. dist. scribed T2S R35E S35 BT.

A Pine 26" dia. bears S34°W 67 lks. dist. scribed

T3S R35E S2 BT.
A Tamarack 6" dia. bears N60°E 8 lks. dist. scribed T2S R35E S36 BT.

<u>Index Fi</u>	A Te_No. ≭- 21
DIAGRA	4M
T2S	R35E
35	36
2 T3	1 S

Description of corner evidence found:

FOUND: The original NE bearing tree, a Tamarack (dead) 12" dia. with opened scar and visible scribing "S" on a SW face. At record bearing and distance set a point from which a 32" dia. pine mostly rotten and lying on the ground with visible scribing "5E BT" bears S34°W 44.0 ft. No evidence could be found of the SE or NW BT's.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the True Corner Point established by reference to the remains of the original BT's described above, we set a 2 1/2"x 30" galvanized pipe 20" in the ground with mound of stone to cap with 3" brass cap stamped: From which:

A Lodgepole Pine 7" dia. bears N65°E 14.2 ft. scribed T2S R35E S36 BT

A White Fir 5" dia. bears N53°W 44.9 ft. scribed T2S R35E S35 BT.

A Douglas Fir 9" dia. bears S41°W 40.7 ft. scribed T3S R35E S2 BT.

A Tamarack 6" dia. bears S53° E 17.6 ft. scribed T3S R35E

Attached 54-3 and 54-4 signs to all BT's. Attached brass washer stamped LS 1099 to foot blaze of all BT's. Painted blazes and 6" band around all BT's red. Attached 54-4 sign to metal fence post set 5' East.

Compass Declination: 18 $1/2^{\circ}$ East. I hereby certify that the above described corner monument and/or accessories was established as described on June 18, 1981.

Witnesses: Glen Wagoner Millard Wyatt

REGISTERED PROFESSIONAL LAND SURVEYOR
Hary L. Langle
OREGON O JULY 22, 1977 GARY L. LANGLITZ 1099

5'e No. 400-84 R

T2S

S35

S2

T3S

1981

OR PLS 1099

R35E

\$36

S1

R35E

Office of Surveyor	County of Union	
state ofOregon	I hereby certify that the within instrument was filed	in this office SURVEYOR
(COUNTY OFFICIAL		Pata Received
Form R6-7100-57 (9/71)		The Filed
		Ву