## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishments

Corner established in 1883 by General Land Office by contract survey

Original survey record states; Set a basalt stone 16x16x14 inches 11 inches in ground for corner to sections 7,8,17 and 18, from which; A fir 24" in diam. bears N27°E 122 lks. dist. marked

T3S. R35E S8BT.

A pine 6" in diam bears N63°W 84 1ks dist marked T38, R35E S7BT.

A fir 20" in diam bears S57°E 62 lks. dist. marked T3S R35E S17BT; A fir 10" in diam bears S37°W 204 lks dist marked T3S R35E S18BT;

J-5 DIAGRAM T3S R35EWM.

## Description of corner evidence found:

The stone was not found. A fir 24" in diam bears S57°E 62 lks with scribe visible.

> REGISTERED OREGON AND SURVEYOR MES G. VOELZ 381

Description of monument and accessories I established to perpetuate the

At the position of the corner I set a 2" galvanized pipe 30" long with bronze cap and 8" platewelded to bottom.

I stamped the disk

COR **T3S** R35E

File No. 406-84 R

From the pipe monument the original tree is: A fir 24" in diam bears S57°E 62 lks dist. S18\$17 I also established new bearing trees as follows; ORE LIC 381 A fir 10" in diam bears N10°W 58 ft. dist. marked 1969 T3S, R35E S7BT; A fir 12" in diam bears N27°E 61.5 ft. marked T3S, R35E S8BT; A fir 18" in diam. bears S59°W 141.6 ft dist. marked T3S R35E S18BT. (Trees are measured to respective centers and marked with scribe) I placed a steel fence post at the corner with USFS sign 54-4 attached and a National Forest Boundary sign indicating National Forest land to the North. I also placed USFS bearing tree signs on the bearing trees shoulder high facing the corner.

Office ofCountysurveyor	I SURVEYOR
for record on the27 day of .Aug	Qate Received
	Date Filed
	Ву