


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner established in 1882 by Rufus S. Moore under General Land Office contract no. 451. Surveyor General Record States;

Set basalt stone 15"x10"x5" for cor. to sections 15-16-21-22 marked with 3 notches on S. and E, edges, Raised mound of stone along side.



No other record of remonumentation found in the county record.

Description of corner evidence found:

Found large mound of stone.
I did not find a marked stone.
Accepted stone mound on the basis of it being within 2.0 feet east-west, and 7.0 feet north of corner proportion.

Description of monument and accessories I established to perpetuate the

original location of this corner I set a 2 1/2"x30" galvanized iron pipe with brass cap 16" in the ground at the center of the rock mound and raised a large mound of stone, from which;
New BT.


A pine 30" in diameter bears N 61 E 242.4 feet in distance marked T 3 S R 35 E S 15 BT.

No other trees within limits.

I placed a nail and a brass washer marked O.P.L.S. 991 at the BT. blaze.

I used a steel tape and a magnetic compass with 20 degrees East declination set into the compass.

I set a steel fence post with sign 5.0 feet east of the corner.



REGISTERED PROFESSIONAL LAND SURVEYOR

Gregory T. Blackman

OREGON
EX. 3, 978
GREGORY T. BLACKMAN
991

Office of Surveyor County of Union
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 18 day of Sept, 1978
J. Voelz by J. Lyle
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR

Date Received _____

Date Filed _____

By _____

File No. 422-84 R
WGPO 796-333