

33-69A

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


12

N-23

History of original corner establishment:

Corner established in 1882 by General Land Office.
Contract survey.

Original notes read. Set a basalt stone 12x11x6 inches 8 ins in ground for $\frac{1}{4}$ cor marked ~~to~~ north face from which;
A pine 36" in diam bears N63°W 92 lks dist marked $\frac{1}{4}$ SBT
A pine 9" in diam bears S59°W 143 lks dist marked $\frac{1}{4}$ SBT.



Description of corner evidence found:

Found stone of record.

Aspine 30" in diam bears N63°W 92 lks dist with scribe visible.

REGISTERED
OREGON
LAND SURVEYOR


James G. Voelz

MAY 4, 1969
JAMES G. VOELZ
381

Description of monument and accessories I established to perpetuate the original location of this corner

At the position of the corner I set a 2" galvanized pipe 30" long and with a 8" plate welded to bottom of pipe and a bronze cap on top. The pipe was set at a depth of 18" and backfilled with stone and soil and stone monument was raised around the pipe. The marked stone was placed along side the pipe.

I stamped the disk.



From the corner the original bearing tree is.

A pine 30" in diam bears N63°W 92 lks dist marked with scribe $\frac{1}{4}$ SBT. I set additional bearing tree; A fir 11" in diam bears S50°W 72.5' marked with a scribe $\frac{1}{4}$ SBT. A steel fence post was set with USFS sign 54-4 attached. USFS National forest signs were attached to post indicating National Forest Land to North, USFS bearing tree signs were placed on the bearing trees shoulder high and facing the monument.

Office of County Surveyor County of UNION
State of Oregon I hereby certify that the within instrument was filed in this office
for record on the 2. day of Sept., 1969, at o'clock A. (signed)
..... County Surveyor by
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY
SURVEYOR

Date Received _____

Date Filed _____

By _____

File No. 427-84R