CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original Survey by General Land Office, Contract survey 1882. The original notes read; Set a basalt stone 17x10x7 ins. 12 ins in the ground from which; A pine 36" in diam bears N80°E 260 lks dist. marked ‡SBT.

A pine 6" in diam bears S74°E 270 lks dist marked ‡SBT.

<u> </u>		
DIAGRAM		
T3S R35EW	M	
<u>\$25</u> \$36	_	
536		

Description of corner evidence found:

Found stone at the mound of stone with \$\frac{1}{4}\$ marking.

Found - A pine 24" in diam bears \$74. E 179.3 ft. with scribe visible.



Description of manument and accessories I established to perpetuate the original location of this corner

At the location of the stone I set a 2^N galvanized pipe 30^N long with a 8^N plate welded to bottom and a bronze cap on top. The pipe is set to a depth of Approx. 1 ft. and hole is backfilled with stone and soil and raised a stone mound. Set the marked stone by the pipe.

I stamped the disk.

T3S R35E

S25
S36

ORE LIC 381

1969

File No. 432-84 R

From the pipe the original bearing tree is: A pine 24" in dam. bears 574°E 179.3 ft.

I set a additional bearing tree. A pine 48" in diam bears N27°E
480 ft. dist. Marked \$SBT. A steel fence post was set with USFS sign 54-4
attached. A National Forest Boundary sign was attached to post indicating
National Forest Land to the East. USFS bearing tree signs were placed on the
bearing trees shoulder high facing the monument. (Distance measured to
BT scribe on the tree)

Office of	YOR County of UNION	UNION COUNTY
State of Ure gon I here	by cortify that the wishin in a	PORAFAOR
Co. Surveyor	t. 19169, a 1	Note: Received
	DEPUTY	Date Filed
		Ву