## OREGON CORNER RESTORATION FORM

Section 36 Township 3S Range 35E

Date 5-03-95 County Union

CORNER DESIGNATION: X-2

Previous Renewals/Surveys, etc. This corner was originally set by U.S. Deputy Surveyor J. Hurlburt under contract No. 201 dated August 5, 1863. The Surveyor Generals notes state: Set basalt stone 20 x 12 x 6 10 in. in ground and made mound of stone 2 ft. high for 1/4 sec. cor.

Monument(s) & Accessories Found: (Condition and Source) Found a rough unmarked 20 x 12 x 6 inch basalt stone and a mound of stone on a rocky, open east facing slope, approximately 300 feet west of a north-south fence.

Monument Detail: TOMKINS SURVEYING

T3S s35 ----836 1/4 1995 WA 25893 OR 2360

Monument Set (Procedures and Description): At the position of the found basalt stone, set a 5/8"x 30" rebar 20" in the ground with a 2" aluminum cap stamped as shown in the monument detail and surrounded with a mound of stone.

## New Accessories:

A 5/8"x 30" rebar with a yellow plastic cap stamped "TOMKINS SURVEYING" bears N 49 1/2 E 13.59 feet.

N 49 1/2°E 13.59 feet. A 5/8"x 30" rebar with a yellow plastic cap stamped "TOMKINS SURVEYING" bears S 40°E 19.14 feet.

A 5/8"x 30" rebar with a yellow plastic cap stamped "TOMKINS SURVEYING" bears

S 58'W 16.73 feet.
A 5/8"x 30" rebar with a yellow plastic cap stamped "TOMKINS SURVEYING" bears 10.73 feet. N 51°W

located on Location & Comments: This corner is an open east slope approximately 300 feet west of a north-south fence. The position of this corner is very nearly at the midpoint between the found N.E. corner of section 36 and the calculated position of the S.E. corner of section 36 as shown on survey No. 012-1995.

Compass Declination: 18° E Surveyor's Seal

Firm/agency: Tomkins-wells Joint Venture

Land Surveying P.O. Box 1696

Party Chief: Greg Flowers

Notes: Greg Flowers Witness: Todd Rosenbalm

REGISTERED Pendleton, Oregon 9780 COUNTY PROFESSIONAL LAND SURVEYOR ins

OREGOR JULY 26, 1988 PAUL W. P. TOMKINS JOHO

renews 6/30/96 5/07/95