

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


Z-17

History of original corner establishment:

The original corner was established on May 16, 1874 by John A. Hurlburt under GLO contract No. 201, as follows:

Set a basalt stone 30" x 12" x 6", 12" into the ground and made a mound of stones 2 feet high for the corner from which:

A pine, 24" in diameter, bears N 82° E, 287 links (189.42 feet). No other trees near.



Description of corner evidence found:

The original stone is broken into three pieces and is in a mound of stones. I fit the pieces together and find 4 notches on the broken edge.

A fairly large burnt pine stump of indeterminate size bears N 76° E, 191.2 feet. No blaze or scribes remain.

|                       |                     |
|-----------------------|---------------------|
| UNION COUNTY SURVEYOR |                     |
| Date Received         | 12-2-87             |
| Date Filed            | 12-8-87             |
| By                    | G. LANGRISH, Deputy |
| File No.              | 167-87 R            |

Description of monument and accessories I established to perpetuate the original location of this corner

Moving the corner stone aside, I set in it's place a 2 1/2" x 30" galvanized iron pipe with a 2 1/2" brass cap attached 12" into the ground in a mound of stones to the top of the cap. The cap is marked as shown in the diagram. The original stone pieces are placed in the mound at the base of the iron pipe.

From which new bearing trees:

A 16" ponderosa pine bears N 54° E, 183.5 feet scribed "T2S R36E S35 BT" on a single blaze.

A 28" ponderosa pine bears S 73° E, 215.6 feet scribed "T3S R36E S2 BT" on a single blaze.

A 11" ponderosa pine bears S 74° W, 126.0 feet scribed "T3S R36E S3 BT" on a single blaze.

A 16" ponderosa pine bears North, 114.1 feet scribed "T2S R36E S34 BT" on a single blaze.

A 3 foot steel post with a land survey monument sticker attached is set to the east of the monument.

Each bearing tree has a 3/4 inch brass washer, marked "PLS 1636", nailed flush with the blaze between the scribed "B" and "T", and bearing tree and land survey monument signs nailed above the blaze in addition to a red painted blaze and band around the tree.

I hereby certify this corner position was perpetuated as hereon described on November 4, 1987. De. 20° E. Witnesses: John Bunce and Bob Erdman.

Office of County Surveyor..... County of Union.....  
State of Oregon....., I hereby certify that the within instrument was filed in this office  
for record on the ..... day of .....  
..... by .....  
(COUNTY OFFICIAL) (DEPUTY)

