
UNION COUNTY CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by John H. Hurlburt under GLO Contract Number 201, dated August 5, 1873. Surveyor General record states:
Set Stone 20x10x8 inches marked % in a mound of stone for % Sec. Cor.
The Union County surveor, J.W.Kimbrell reset this corner in 1888, page 114 in the Old Survey Volume.
Kimbrell states: Set volcanic rock 7"x7"x20" for 1/4 cor.



No record of subsequent monumentation found in Union County survey records.

Description of corner evidence found:

Found no evidence of either original corner monument stone.

The center of search area is now in the Grande Ronde River.

See map of Survey Number 028-1992.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the proportionate position, determined by survey, I set a Steel fence post, in the center of the Grande Ronde River, from which;

New Bearing Trees or Object;
A 2-1/2x30 inch aluminum pipe with aluminum cap bears N44°16'31"E, 343.46 feet marked T3S R36E % S15 RM 343 46 1992 OPLS 644.
A 2-1/2x30 inch aluminum pipe with aluminum cap bears N17°16'35"W, 378.80 feet marked T3S R36E % S16 RM 378.80 1992 OPLS 644.
A 23 in. dia. Ponderosa Pine bears N26°E, 352.21 feet mk'd 1/4 S 15 BT A 23 in. dia. Ponderosa Pine bears N31°W, 418.48 feet mk'd 1/4 S 16 BT

I hereby certify that the above corner point was perpetuated as hereon described on July , 1992.

Witness: Jim Bennett Peter Crabtree

> PROFESSIONAL AND SURVEYOR

REGISTERED

DUANE I. GRIFFITM 644 I used a steel tape and magnetic compass in the establishment of new accessories. I used 20° East magnetic declination and the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 644 to the BT blaze.

Detr Faccived 11/23/92

By Aug Block

File No. 125-1992 R

L-13 6113