
UNION COUNTY CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner was never established.



No record of subsequent monumentation found in Union County survey records.

Description of corner evidence found:

See Map of Survey Number 028-1992.

Description of monument and accessories I established to perpetuate the original location of this corner:

At position, determined by survey I set a 2½"x30" aluminum pipe with aluminum cap marked as shown, 12 inches in the ground, from which;


New Bearing Trees or Object;
A 22 inch diameter Ponderosa pine bears N54°E, 142.87 feet marked CN ¼ S14 BT
A 15 inch diameter Ponderosa pine bears S73°E, 261.6 feet marked CN ¾ S14 BT
A 5/8" X 30" rebar with aluminum cap bears S18°W, 7.08 feet marked T3S R36E ¼ S14
RM 1992 OPLS 644.
A 4½'x6'x6' Basalt boulder bears N56°W, 49.82 feet marked X BO, on SE face.

Raised a mound of stone, 3 foot base to top of cap. Set a steel fence post approximately 5 feet North. with a 54-9 sign attached.

I hereby certify that the above corner point was perpetuated as hereon described on July 31, 1992.

Witness: Jim

Jim Bennett Pete Crabtree Jeff Peterson



REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON JULY 10, 1964 DUANE I. GRIFFITH I used a steel tape and magnetic compass in the establishment of new accessories. I used 20° East magnetic declination and the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 644 to the BT blaze.

UNITED COMPATY
SEEDWAY 12

Date Received 1//23/92

Dete Filed 1//28/92

By Hug Block
File No. 128-1992 R

L-19 6119

1-21