
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by J.W. Kimbrell, Union County Surveyor on survey for Robert Young dated December 4, 1888, and recorded as survey number 56 on page 114 of the old book of surveys. His record states:

Set post for 1/8 corner from which; a fir 7 inches dia bears N85°W 109 lks dist a fir 7 inches dia bears S69°E 125 lks dist



No record of subsequent monumentation found in Union County survey records.

Description of corner evidence found:

Found no evidence of the Kimbrell corner or it's accessories. See Union County Survey Number 25-89

Description of monument and accessories I established to perpetuate the

original location of this corner: At position determined by survey, I set a 2½" x 30" aluminum pipe with aluminum cap marked as shown, 29 inches in the ground, from which;

New Bearing Trees; A 12 inch diameter Douglas Fir bears S7°E, 27.80 feet marked E1/16 S21 BT (Spike on left) A 13 inch diameter Western Larch bears N29°W, 29.63 feet marked E1/16 S16 BT

Painted a 6 iuch red band around all BTs and attached Bearing Tree and Land Survey Monument signs

Set a steel fencepost approximately 5 feet North with Land Survey Monument sign attached.

I hereby certify that the above corner point was perpetuated as hereon described on October 2, 1989.

Witness: Jeff Petersen



REGISTERED **PROFESSIONAL** LAND SURVEYOR 19119 7.360.Km OREGON GREGORY T. BLACKMAN

I used a steel tape and magnetic compass in the establishment of new accessories. I used 17° magnetic declination. The distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 991 to the BT blaze.

Office of	County of	********************************
State of / here	by castify that the within instrument	was filed in this office
for record on the day of	UNION COUNTY	
(COUNTY OFFICIAL)	ID5P)TY)
	Data Passived 11-14-89	

Form R6-7100-57 (9/71)

*GPO-591-971, 1988

N - 12

2-6