


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

None Set

Index File No. Q-5



Description of corner evidence found:

Description of monument and accessories established to perpetuate the original location of this corner: At surveyed point set 2½"x30" galvanized pipe with brass cap stamped:
Set pipe 15" in ground to rock with mound of stone to cap.
From which:

A P. Pine 17" in dia. bears N48°E, 138.3 ft., scribed S 1/16 S20BT.


A Douglas Fir 14" in dia. bears S12°W, 95.6 ft., scribed S 1/16 S19BT.

Attached 54-3 signs to both BT's. Attached brass washer stamped LS 1294 to foot blaze of both BT's. Painted blazes and 6" band around both BT's red. Attached 54-2 and 54-4 signs to metal fence post 5' West of corner. Attached 54-2 and 54-9 signs to metal fence post 5' North of corner.

T3S R36E WM
S 1/16
S19 — S20
1979
OR PLS 1294

I hereby certify the above corner monument was established as herein described.
November 21, 1979

Witnesses: G. Wagoner
D. Allen



Office of.....County Surveyor..... County of..... Union.....

State of..... Oregon..... I hereby certify that the within instrument was filed in this office

for record on the..... day of....., 19...79

..... by.....
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR

Date Received _____
GPO 799 509
Date Filed _____
By _____
File No. 444-84R