


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

-10-

History of original corner establishment:

None set.

Index File No. R-4



Description of corner evidence found:

Description of monument and accessories established to perpetuate the original location of this corner: At surveyed point set 2½"x30" galvanized pipe with brass cap stamped:
Set pipe 15" in ground to rock with mound of stone and soil to cap.

T3S R36E WM
S19
E 1/16 ———|
S30
1979
OR PLS 1294

From which:

A Douglas Fir 10" in dia. bears S23°E, 24.5 ft., scribed E 1/16 S30BT.

A P. Pine 16" in dia. bears N83°W, 84.5 ft., scribed E 1/16 S19BT.


Attached 54-3 signs to both BT's. Attached brass washers stamped LS 1294 to foot blaze of both BT's. Painted blazes and 6" band around both BT's red. Attached 54-2 and 54-4 signs to metal fence post 5' East of corner. Attached 54-2 and 54-9 signs to metal fence post 5' North of corner.

I hereby certify the above corner monument was established as herein described.

November 13, 1979

Witnesses:

- G. Wagoner
- D. Allen
- M. Wagoner
- G. Lester



Office of.....County Surveyor..... County of.....Union.....

State of.....Oregon....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19..79

..... by (COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR	
Date Received _____	☆ GPO 799-509
Date Filed _____	
By _____	
File No. <u>447-84 R</u>	