


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner established in 1873 by J. Hurlburt, under General Land Office Contract No. 201
Surveyor General's records state:
Set fir post 4 ft. long, 3 in. thick, 2 ft. in ground for 1/4 Sec. Cor.
Pine 24 in dia. N25⁰W, 71 lks.
Fir 18 in. dia. S12⁰W, 65 lks.

Index File No. R-7



Description of corner evidence found: Could find no trace of original corner post. Found Douglas Fir snag 28" in dia. and 12' tall with open upper blaze charred but with faint scribing visible for Southwest BT. Found 26" down and decayed P. Pine with visible scribing in upper blaze "1/4S" for Northwest BT.

Description of monument and accessories established to perpetuate the original location of this corner: At record bearing and dist. from standing snag set 2 1/2"x30" galvanized pipe with brass cap stamped:
Set pipe 20" in ground with mound of stone to cap.
From which:

T3S R36E WM
1/4 ———
S20
S29
1979
OR PLS 1294

A Douglas Fir 16" in dia. bears N9⁰E, 4.2 ft., scribed 1/4S20BT.
A Douglas Fir 12" in dia. bears S46⁰W, 10.6 ft., scribed 1/4S29BT.
Attached 54-3 signs to both BT's. Attached brass washer stamped LS 1294 to foot blaze of both BT's. Painted blazes and 6" band around all BT's red. Attached 54-4 sign to metal fence post 5' West of corner.

I hereby certify the above corner monument was re-established as herein described on November 7, 1979.

WITNESSES: R. Orton
D. Allen
L. Huntsman

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Howard L. Perry
**OREGON
SEPTEMBER 23, 1977
HOWARD L. PERRY
1294**

Office of..... County Surveyor..... County of..... Union
State of..... Oregon....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19..79
..... by
(COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY
SURVEYOR**
Date Received _____
Date Filed _____ ☆ GPO—798-276
By _____
File No. 449-84R