


Index
 File No. T 13
 T 3S R. 36E R.D. La Grande County Union Tract or Survey No. _____ Cor. W 1/4 Cor. No. Sec. 27
 Merid. Willamette N.F. W-W State Oregon

CORNER RECORD (SEARCH)
 (Ref. FSM 7151.4)

CORNER DIAGRAM



DESCRIBE CORNER MONUMENT FOUND

Basalt stone 12 x 6 x 6 inches, 6 inches above ground in good condition with 1/4 on West face

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

PHOTO IDENTIFICATION DATA

Photo No. _____
 Filed At. _____
 Object Ident. _____
 Ident. By _____
Signature

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

Located on steep N slope in DF reprod with occasional PP
 A state Board of Forestry location poster on a green 32" pp bears about N. 15° E. 2 chs. dist. Corner is also about 30' N. of a old log road course NW. I can't understand why the surveyor didn't scribe a BT here

PLANE COORDINATE POSITION DATA

State _____ Zone _____
 X _____
 Y _____
 Estab. By _____
Agency

Signature
 John Mitchel

Title _____ Division _____ Headquarters _____

Date 9/3/76 7100-52-(3/68)

UNION COUNTY SURVEYOR
 Date Received _____
 Date Filed 12-21-87
 By G. LANGLITZ, DEPUTY
 File No. 267-87R


T-13

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by John A. Hurlburt under GLO contract number 201, dated August 5, 1873. Surveyor General record states:

Set basalt stone 15x14x12 8 in in ground for 1/4 sec cor



No record of subsequent monumentation found in Union County survey records.

Description of corner evidence found:

Found a stone 18x16x7 inches marked 1/4, firmly set 8 inches in the ground.

See Union County Survey Number 25-89

Description of monument and accessories I established to perpetuate the

original location of this corner: In place of the found original corner stone, I set a 2 1/2" x 30" aluminum pipe with aluminum cap marked as shown, 29 inches in the ground, from which:

New Bearing Trees;

A 8 inch diameter Western Larch bears N56°E, 20.86 feet marked 1/4 S27 BT

A 10 inch diameter Ponderosa Pine bears N89°W, 44.60 feet marked 1/4 S28 BT

Buried the original corner stone North and alongside monument.

Painted a 6 inch red band around all BTs and attached Bearing Tree and Land Survey Monument signs.

Set a steel fencepost approximately 5 feet North with Land Survey Monument sign attached.

I hereby certify that the above corner point was perpetuated as hereon described on October 1, 1989.

Witness: Jeff Petersen



**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Gregory T. Blackman

OREGON
JULY 13, 1973
GREGORY T. BLACKMAN
991

I used a steel tape and magnetic compass in the establishment of new accessories. I used 17° magnetic declination. The distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 991 to the BT blaze.

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of.....

(COUNTY OFFICIAL)

UNION COUNTY
by **SURVEYOR**
(DEPUTY)

Date Received 11-14-89

Date Filed 11-14-89

By R. ROBINSON, DEPUTY

File No. 204-89 R

Form R6-7100-57 (9/71)

*GPO-591-971, 1988