CERTIFIED RECORD OF LAND CORNER MONUMENTATION


HISTORY OF ORIGINAL CORNER ESTABLISHMENT:

Corner originally established by William H. O'Dell under GLO contract Number 120, dated May 27, 1867. Surveyor General record states:

Set post for corner from which;


A tamarack 14 ins. dia. bears S 75°W, 138 lks dist.

A pine 30 ins. dia. bears S85°E, 40 lks dist



No record of subsequent monumentation found in Union County survey records **DESCRIPTION OF CORNER EVIDENCE FOUND:**

There has been a great deal of disturbance in the area.



See Union County Survey Number 1993-020.

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:


The proportionate position of this corner is on the northerly bank of Rock Creek and would be subject to being washed out, therefor; At a point 20 feet northerly on the section line from the proportionate position as determined by survey, I set a 2½" x 30" aluminum pipe with aluminum cap marked as shown, 30 inches in the ground, marked as shown, from which;

NEW BEARING TREES:

A 12 inch diameter Ponderosa Pine bears N41°E, 166.56 feet marked 1/4 S 5 BT A 13 inch diameter Ponderosa Pine bears S81°E, 219.67 feet marked S E BT A 14 inch diameter Ponderosa Pine bears N31°W, 162.13 feet marked 1/4 S 6 BT

A 15 inch diameter Cottonwood bears N67°W, 50.23 feet marked 1/4 S6 BT

Set fence post 4± feet South with attention sign.



I hereby certify that the above corner point was perpetuated as hereon described on June 3, 1993.

Witness; Travis Foster



I used a steel tape and magnetic compass in the establishment of new accessories. I used 20° East magnetic declination and the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 644 to the BT blaze.