


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:

None.



DESCRIPTION OF CORNER EVIDENCE FOUND:


None.

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED.

At the proper position computed per the 1973 Manual of instructions I set a 1" x 24" iron rebar with a 2" aluminum cap 20" in the ground. I set an 18" collar of stone around the Cap. The cap was stamped as shown below.

I marked two bearing trees. Each bearing tree has a copper nail with a 1 1/8" head stamped WTS and 56295LS driven between the letters B & T. Measurements were taken to the dent in the head of the nail with a Trimble 5601 electronic total station. Bearings are based on the survey control for County Survey No. 032-2004.

An 18" Ponderosa Pine bears S55°57'39"W, 59.54', scribed SE 1/16 S31 BT.
A 13" Ponderosa Pine bears S77°14'57"E, 75.65', scribed SE 1/16 S31 BT.



I hereby certify that the above corner point was established as hereon described on August 27, 2004.

Witness: Kyle Lathrop
David Haddock

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Stephen K. Haddock

OREGON
JULY 9, 2001
STEPHEN K. HADDOCK
56295LS

RENEWAL DATE 6-30-05

UNION COUNTY
SURVEYOR

Date Received 12/8/04

Date Filed 12/10/04

By R. ROBINSON, Deputy

File No. 068-2004-R