

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:

Survey No. 4-69 by James Voelz, originally accepted fence line as North line of NE 1/4 of SW 1/4 of Section 3. Survey No. 5-71, 62-71 and 72-71, also completed by James Volez, accept the railroad tie fence corner as Center-West 1/16th corner. Subsequently accepted by Survey No. 1-73 and 21-76 and Minor Partition 20070013T.

DESCRIPTION OF CORNER EVIDENCE FOUND:

Found railroad tie fence corner.

SEE SURVEY NUMBER 008-2008

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:


NEW BEARING OBJECTS:

A 5/8" x 30" Iron Pin with 1 1/2" Aluminum Cap, bears South 88°38'55" East, a distance of 15.00 ft., marked E RP 15 FT.

A 5/8" x 30" Iron Pin with 1 1/2" Aluminum Cap, bears South 0°00'42" West, a distance of 15.00 ft., marked S RP 15 FT.

I hereby certify that the corner was perpetuated on 20th of March 2008.

Witnesses: Jeff Hsu



**UNION COUNTY
SURVEYOR**

Date Received 3/18/08

Date Filed 4/5/08

Filed By [Signature]

File Number 003-2008R

REGISTERED
PROFESSIONAL
LAND SURVEYOR

[Signature]

OREGON
July 17, 1986
RICK G. ROBINSON
2219

Renewal Date: December 31, 2008

I used a Leica Series 530 GPS in the establishment of the new accessories. The basis of bearing is the same as Survey No. 008-2008. Distances are to the center of the aluminum cap.

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


HISTORY OF ORIGINAL CORNER ESTABLISHMENT:

Survey No. 4-69 by James Voelz, originally accepted fence line as North line of NE 1/4 of SW 1/4 of Section 3. Survey No. 5-71, 62-71 and 72-71, also completed by James Volez, accept the railroad tie fence corner as Center-West 1/16th corner. Subsequently accepted by Survey No. 1-73 and 21-76 and Minor Partition 20070013T.

DESCRIPTION OF CORNER EVIDENCE FOUND:
Found railroad tie fence corner.

SEE SURVEY NUMBER 008-2008

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:



NEW BEARING OBJECTS:

A 5/8" x 30" Iron Pin with 1 1/2" Aluminum Cap, bears South 88°38'55" East, a distance of 15.00 ft., marked E RP 15 FT.

A 5/8" x 30" Iron Pin with 1 1/2" Aluminum Cap, bears South 0°00'42" West, a distance of 15.00 ft., marked S RP 15 FT.

I hereby certify that the corner was perpetuated on 20th of March 2008.

Witnesses: Jeff Hsu

**UNION COUNTY
SURVEYOR**

Date Received 3/18/08

Date Filed 4/5/08

Filed By *James T. O'Leary*

File Number 003-200812

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Rick G. Robinson
OREGON
July 17, 1986
RICK G. ROBINSON
2219

Renewal Date: December 31, 2008

I used a Leica Series 530 GPS in the establishment of the new accessories. The basis of bearing is the same as Survey No. 008-2008. Distances are to the center of the aluminum cap.