


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:
Survey No. 017-2009 position only

T 3 S R 38 E D-16



DESCRIPTION OF CORNER EVIDENCE FOUND:

NONE

See Union County Survey Number 002-2014

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At position determined by survey, I set a 5/8"x30" iron pin with
2 1/2" aluminum cap marked as shown, 30" in the ground, from which:

NEW BEARING OBJECTS:


A 5/8"x30" iron pin with yellow plastic cap marked "BGB SURVEY MARKER" set by survey number 017-2009
bears North 0°15'18" East, a distance of 4.17 feet,

A 5/8"x30" iron pin set by survey number 94-77 bears North 73°08'53" East, a distance of 14.32 feet,

I hereby certify that the corner was referenced on March 21, 2014.

Witness: Jeff Hsu

REGISTERED
PROFESSIONAL
LAND SURVEYOR



OREGON
July 17, 1986
RICK G. ROBINSON
2219

Renewal Date: December 31, 2014

BAGETT - GRIFFITH & BLACKMAN

T3S R38E

SE 1/16 S 3

2014
OPLS 2219

**UNION COUNTY
SURVEYOR**

Date Received 3/24/14

Date Filed 3/24/14

Filed By [Signature]

File Number 009-201412

I used a Leica GS 15 GPS unit in the establishment of the new accessories. The basis of bearing is the same as Survey No. 002-2014. Distances are to the center of the pins.