

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


**History of original corner establishment:**

Corner originally established by David T. Thompson under GLO contract number 103, dated september 3, 1863. Surveyor General record states:

Set post for 1/4 section corner in mound of earth with pits trench charred stake as per instructions.

Corner subsequently remonumented by surveyors unknown and at a date unknown. A concrete pyramid 12" square on the bottom and 7" square at the top, 24" high with a lead plug and brass screw on the top was first referenced by James Voelz on survey number 4-62. Mr. Voelz called this the 1/4 corner

Corner again used on survey number 12-84 as the quarter corner.



**Description of corner evidence found:**

Found a concrete monument 7"x12"x24" with a lead plug set inside a pipe and a brass screw in the lead plug. It should be noted that A.H. McLain used this style of monument in 1922 survey of LaGrande.

**Description of monument and accessories | established to perpetuate the**

**original location of this corner:** At the monument position I set a 2 1/2"x30" aluminum pipe with aluminum cap marked as shown 26" in the ground with a small mound of stone around cap. Removed concrete monument in its entirety. No Bts available.

Corner sets in an East West fence, 3.5 feet East of a fence corner to an East-West-North -South fence.

Corner set 4/23/87

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Gregory T. Blackman*

OREGON  
JULY 13, 1973  
GREGORY T. BLACKMAN  
991

UNION COUNTY  
SURVEYOR

Date Received 4-28-87

Date Filed 4-30-87

By G. LANGRIZ, Deputy

File No. 14-37 R

GRIFFITH  
T3S R38E \*  
1/4  
S 17                  S 16  
1987  
OPLS 991

BAGETT ASSOC.

Office of..... County of.....  
State of....., I hereby certify that the within instrument was filed in this office  
for record on the..... day of....., 19.....  
..... by .....

(COUNTY OFFICIAL) (DEPUTY)

# HORIZONTAL CONTROL DATA

UNION COUNTY, OREGON  
OREGON STATE PLANE, NORTH ZONE (3601)

STA. NAME: 9313

QUARTER CORNER : 17 / 16

TWP. 3 S. RGE.38 E.

DATE SET: OCT. 1993

SURVEYOR: WALTER L. CASWELL  
PLS 737

FIRM: EAGLE GPS SURVEY CORP  
13545 NW SCIENCE PARK DR  
PORTLAND, OR. 97229  
(503) 643-1073

GEODETIC COOR: NAD 83(91)

LAT: 45°18'14.36263" N

LONG: 118°04'34.37066" W

SP. COOR: NAD 83(91)

N: 606275.895 INT.FT.

E: 8825612.151 INT.FT.

THETA: 1°43'08.094"

TYPE: GPS

ORDER: SECOND CLASS: 1

SCALE FACTOR: 0.999897362

ELEV: 2906.00 US.FT.

ELEV. DATUM: NGVD 29

\*\*\*\*\*  
DIRECTIONS "TO REACH": FROM 20TH STREET AND FOOTHILL ROAD IN LA GRANDE HEAD SOUTH ON FOOTHILL ROAD FOR 0.1 MILES TO A CURVE TO THE EAST AND A ROAD INTERSECTION TO THE RIGHT. TURN ONTO THE SIDE ROAD AND CONTINUE SOUTH HEADING UPHILL UNTIL YOU COME TO A CEMETERY. ENTER THE CEMETERY (ALONG A FENCE LINE ON YOUR RIGHT) TO A POINT WHERE YOU MUST TURN LEFT. STOP HERE AND WALK SOUTH TO A FENCE CORNER (N-S-E-W) A SHORT DISTANCE UP THE HILL. THE MONUMENT IS A 5/8" IRON ROD WITH A 2 1/2" ALUMINUM CAP 3.5 FEET EAST AND 0.7 FEET SOUTH OF THE FENCE CORNER.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Walter L. Caswell*

OREGON  
JULY 8, 1966  
WALTER L. CASWELL  
737

EXPIRES 12/31/95

1 METER = 3.280833333333... U.S. FEET = 39.37 INCHES

1 METER = 3.280839895 INT'L FEET OR 1 INCH = 2.54 CM.

TO CALCULATE ELEVATION FACTOR (IN THE NORTH AMERICAN CONTINENT)

DIVIDE 20,906,000 BY (20,906,000 + ELLIPSOID ELEV. IN FEET)

SHEET 14 OF 37