
## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

## HISTORY OF ORIGINAL CORNER ESTABLISHMENT:

Corner originally established by David P. Thompson under GLO contract no. 103, dated September 3, 1863. Surveyor General record states:

I set post for 1/4 corner to secs 16 and 21, in mound of earth, dug



No record of subsequent monumentation found in Union County survey records.

## Description of corner evidence found:

Fence corner, fences N-E-W. These fences have been here for many years. Other surveys in the area have shown the harmony of this position as the one quarter corner. I accept this position as the 1/4 corner common to sections 16 and 21 on the basis of best available evidence.

See Union County Minor Partition No. 1994-010

## DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the position as described above, I set a  $2\frac{1}{2}$ " x 30" aluminum pipe with aluminum cap marked as shown below, 25" in the ground, from which;

A 5/8" X 30" rebar bears N87°E, 5.81 feet, with aluminum cap marked "UNION COUNTY SURVEYOR NE RP"

A 5/8" X 30" rebar bears S21°E, 16.63 feet, with aluminum cap marked

"UNION COUNTY SURVEYOR SE RP"

A 5/8" X 30" rebar bears S81°W, 13.61 feet, with aluminum cap marked

"UNION COUNTY SURVEYOR SW RP"

A 5/8" X 30" rebar bears N10°W, 14.36 feet, with aluminum cap marked "UNION COUNTY SURVEYOR NW RP"

Drove steel fence post 10± feet west, with LCM sign.

TON COMEY SUMVERCA Data Received 7/23/86 Date Filed 8/23/94

GRIFFITH T3S R38E S16 S21 1994 **OPLS 644** 

I hereby certify that the above corner point was perpetuated as hereon described on May 26, 1994.

Witness: Pete Crabtree Travis Foster

> REGISTERED **PROFESSIONAL** AND CHEVITYOR

OREGON JULY 10, 1984 DUANE I. GRIFFITH

I used a steel tape and magnetic compass in the establishment of new accessories. I used 20° East magnetic declination and the distances are to the center of the aluminum cap on the rebar.