
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by David T. Thompson under GLO contract number 103, dated September 3, 1863. Surveyor General record states:

Set post for cor to Secs 2, 3, 10 & 11 in a mound of earth with charred stake pits trench as per instructions



No record of subsequent monumentation found in Union County survey records.

Description of corner evidence found:

Found no evidence of the original corner monument.

I accept an existing Pence corner with fences running North, South and West as the best available evidence of the original corner position.

UNION COUNTY SURVEYOR
Data Received 11-7-91
11 to Filed <u>//-7-9/</u>
CY R. ROBINSON, DEDUTY
File No. <u>024-1991 R</u>

Description of monument and accessories I established to perpetuate the original location of this corner:

At position described above, I set a $2\frac{1}{2}$ " x 30" aluminum pipe with aluminum cap marked as shown, 29 inches in the ground, from which:

New Bearing Objects;
A 5/8"x30" iron pin with 2" aluminum cap marked RM T3S R40E S2 11.82 1991 OPLS 644
bears N32°E, a distance of 11.82 feet
A 5/8"x30" iron pin with 2" aluminum cap marked RM T3S R40E S11 7.80 1991 OPLS 644
bears S43°E, a distance of 7.80 feet
A 5/8"x30" iron pin with 2" aluminum cap marked RM T3S R40E S10 9.14 1991 OPLS 644
bears S32°W, a distance of 9.14 feet
A 5/8"x30" iron pin with 2" aluminum cap marked RM T3S R40E S3 6.31 1991 OPLS 644
bears N51°W, a distance of 6.31 feet
Raised a small mound of stone around monument.
Set a steel fencepost approximately 5 feet South


Set a steel fencepost approximately 5 feet South with Land Survey Monument sign attached.

I hereby certify that the above corner point was perpetuated as hereon described on October 24, 1991.

Witnesses: Greg Blackman and Rick Robinson

REGISTERED

PROFESSIONAL AMD SURVEYOR



OREGON JULY 10, 1964 **DUANE I. GRIFFITH**

I used a steel tape and magnetic compass in the establishment of new accessories. I used 17° East magnetic declination.

Office of	. County of
State of , I hereby certify the	
for record on the day of	
by	***************************************
(COUNTY OFFICIAL)	(DEPUTY)

Form R6-7100-57 (9/71)