
## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

## History of original corner establishment:


Corner not previously established



No record of subsequent monumentation found in Union County survey records.

## Description of corner evidence found:

NONE



## Description of monument and accessories I established to perpetuate the

eriginal location of this corner: At position determined by survey, I set a  $2\frac{1}{2}$ " x 30" aluminum pipe with aluminum cap marked as shown, 18 inches in the ground, from which:

New Bearing Trees and Objects;
A 5/8"x30" iron pin with plastic cap marked BGA SURVEY MARKER bears N40°E, 12.30 feet
A 12 inch diameter Ponderosa Pine bears S46°E, a distance of 28.49 feet marked C¼ S12 BT
A 8 inch diameter Ponderosa Pine bears S78°W, a distance of 48.85 feet marked X BT
A ½"x30" iron pin with plastic cap marked BGA MARKER bears N61°W, a distance of 13.70 feet

Raised a mound of stone around monument, 4 ft. base to top of cap. Painted a 6 inch red band around all BTs and attached Bearing Tree and Land Survey Monument signs. (Attached Bearing Tree signs to the iron pins)

Set a steel fencepost approximately 5 feet South with Property Boundary and Land Survey Monument signs attached.

I hereby certify that the above corner point was perpetuated as hereon described on August 8, 1991.

Witnesses: Rick Robinson, Jim Bennett and John Osterman



OREGON JULY 10, 1984

AND SURVEYOR

REGISTERED

**PROFESSIONAL** 

DUANE I. GRIFFITH

I used a steel tape and magnetic compass in the establishment of new accessories. I used 17° East magnetic declination and the distances to the bearing trees are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 644 to the BT blaze.

Office of	County of
State of , I hereby certify that the within instrument was filed in this office	
for record on the day of	, 19
	by
(COUNTY OFFICIAL)	(DEPUTY)

Form R6-7100-57 (9/71)

★GPO: