

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


History of original corner establishment: Corner originally set in 1864 by Danial T. Thompson under Contract No. 103.

Set post in a mount of stone.

Resurveyed in 1898 by Alonzo Gesner under Contract No. 683.

Remonumented with a basalt stone 20x11x4 ins. Marked with 4 notches on the South and 2 notches on the North, from which:

- A yellow pine 48" in diameter bears S38-30W, 11 lks.
- A yellow pine 14" in diameter bears N83-30W, 70 lks.



Description of corner evidence found:

Found stone, call size properly marked, from which:

- A 50" Pine bears S38W 7.3 ft. blaze evident, healed over.
- A 30" Pine bears N83W 45.2 ft. blaze evident, healed over.

Description of monument and accessories I established to perpetuate the original location of this corner

In place of stone, I set 1"x30" iron pipe with brass cap marked as shown, 26" in ground, from which:


New BT

A 14" Pine bears South 40.5 ft. marked T3S R40E S13 BT.

Buried stone East and alongside pipe.
Used steel tape and magnetic compass with 20° E declination.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 10, 1966
DUANE I. GRIFFITH
644



Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the day of

..... by

(COUNTY OFFICIAL) (DEPUTY)

ION COUNTY
SURVEYOR

Date Received _____

Date Filed _____

By _____

File No. 461-84 R