


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**HISTORY OF ORIGINAL CORNER ESTABLISHMENT:**  
Corner not previously established.



No record of monumentation found in UNION COUNTY survey records.  
**DESCRIPTION OF CORNER EVIDENCE FOUND:**

Corner not previously established.

See Survey Number 027-1997.

**DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:**

At the position determined by said survey, I set a 2 1/2" x 30" aluminum pipe with 2 1/2" aluminum cap marked as shown below, 28" in the ground, from which:

**NEW BEARING TREES:**

- A 19" Douglas Fir bears S 31°E, a distance of 12.65 ft, marked W 1/16 S25 BT.
- A 13" Douglas Fir bears N 48°W, a distance of 34.40 ft, marked W 1/16 S24 BT.

I hereby certify that the corner was monumented on August 19, 1997.  
Witnesses: Rick Robinson, Jeff Madsen and Greg Blackman Jr.


REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Gregory T. Blackman*

OREGON  
JULY 13, 1973

**GREGORY T. BLACKMAN**  
991

*Renewal Date: December, 31 1997*



**UNION COUNTY  
SURVEYOR**

Date Received 8-23-97

Date Filed 8-23-97

Filed By R. Robinson, Deputy

File Number 019-1997R

I used a steel tape and magnetic compass in the establishment of new accessories. The magnetic declination used was 18° East. The distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 991 to the bearing tree blaze.