


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner originally set in 1880, By W.B. Barr under government contract. Contract number was not recorded on notes. Surveyor general notes state; Set stake 4 feet long 4 inches in diameter, 18 inches into the ground, for corner to sections 25, 26, 35, 36, From which BT'S;
 A Tamarack 3 inches in diameter bears S 10 E, 13 links.
 A Fir 12 inches in diameter bears S 47¹/₂ W, 10 links.
 A pine 6 inches in diameter bears N 79¹/₂ W, 48 links.
 A pine 6 inches in diameter bears N 12 E 142. links.



Description of corner evidence found:

Found NW bearing tree stump, scribes visible.

Description of monument and accessories I established to perpetuate the


original location of this corner I set a 2"x36" galvanized pipe with brass cap marked as shown, at the called distance and bearing from the original bearing tree, From which New BT'S.

- A fir 20 inches in diameter bears N 49W, 45.4 feet, Marked T 3 S R 40 E S 26 BT.
- A Fir 15 inches in diameter bears N 29 E, 102.7 feet, Marked T 3 S R 40 E S 25 Bt.
- A Fir 15 inches in diameter bears S 57 E, 23.5 feet, marked T 3 S R 40 E S 36 BT.
- A Fir 18 inches in diameter bears S 31 W, 31.8 feet, marked T 3 S R 40 E S35 BT.

I used a steel tape and a magnetic compass with 20 degrees East declination set into the compass.

See survey number 46-79

REGISTERED PROFESSIONAL LAND SURVEYOR
Gregory T. Blackman
OREGON
JULY 23, 1973
GREGORY T. BLACKMAN
 991



Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office for record on the day of

..... by

(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR

Date Received 4-19-84

Date Filed 4-19-84

By G. LANGLITZ, DEPUTY

File No. 847-84 R

GPO 796-353