

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

E-1


History of original corner establishment:

Corner established by Alonzo Gesner under contract No 683 and dated June 7, 1898.

Surveyor General records state:

Set basalt stone 16 x 12 x 4 ins, 12 ins in the ground at the point of true intersection (18.20 chains S of Cor to Secs 1 and 12 R 40 E) for closing Cor to Secs 6 and 7, marked CC on the E side with 5 notches on the S and 1 notch on the N side, from which:

Marked pine 10" diam brs N13°E, 28 lks dist marked CCT3SR41ES6 BT.
Marked pine 10" diam brs S42½°E, 30 lks dist marked CCT3SR41ES7 BT.



Description of corner evidence found:

Found basalt stone 22 x 16 x 4" with 5 notches on S and 1 notch on N and CC on E face, firmly set in place 6" in ground and projecting 16" out of ground from which:

A rotten tree root brs S42½°E, 30 lks per record with no scribes. No trace of other BT.

UNION COUNTY SURVEYOR	
Date Received	<u>9-1-87</u>
Date Filed	<u>9-16-87</u>
By	<u>G. LANGRISH, DEPUTY</u>
File No.	<u>106-87R</u>

Description of monument and accessories established to perpetuate the original location of this corner:

At position of found stone...

Set 2½" aluminum cap on 2" aluminum pipe 25" in ground & 5" projecting out of ground with surrounding rock mound & 6' fence post alongside with sign 54-9 attached. Cap marked as shown in corner diagram. Buried stone alongside.

New bearing trees established:

A LP pine 9" dia brs N69°E, 24.6' dist mkd T3SR41ES6CC BT.
A LP pine 7" dia brs S60°E, 20.3' dist mkd T3SR41ES7CC BT.

Each BT has a sign 54-3 and signs 54-4 or 54-9 attached below a 6" band of red paint, and each new BT has a brass washer marked PLS 1639 nailed flush with BT blaze.

Compass declination 17° East.

I hereby certify that the above described corner monument was properly remonumented by me and witnessed by Jim DeMastus on August 20, 1987.

Jim DeMastus

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

William L. Hanley

**OREGON
JULY 14, 1978
WILLIAM L. HANLEY
1639**

Office of...County...Surveyor..... County of...Union.....
State of...Oregon..... I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....
..... by
(COUNTY OFFICIAL) (DEPUTY)