


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
Corner not established in original survey.



Description of corner evidence found:

NONE

UNION COUNTY SURVEYOR

Date Received 10-20-86

Date Filed 10-27-86

By G. LANGRISH DEPUTY

File No. 241-86 R


See map of survey number 30-86 filed in the office of the Union County Surveyor
Description of monument and accessories established to perpetuate the original location of this corner: At position determined by survey, I set a 2 1/2"x30" aluminum pipe with aluminum cap marked as shown, 30 inches in the ground and raised a small mound of stone around cap, from which:

A 9 inch White Fir bears S 73° E, 7.45 feet, marked N 1/16 S30 BT.

A 6 inch Douglas Fir bears S 10° W, 5.76 feet, marked X BT.

Set a steel fence post approximately 5 feet North with a 54-9 sign attached.

Corner set : 9/16/86
Witness: Greg Blackman, Rick Robinson



REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON
JULY 10, 1984
DUANE I. GRIFFITH
644

Brass washer marked OPLS 644 nailed to BT blaze. Used steel tape and magnetic compass with 20° East declination. Distances to the BTs are to a 50d Spikeset in right side of tree when facing tree, unless otherwise stated.

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....
..... by

(COUNTY OFFICIAL)

(DEPUTY)