
## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by Alonzo Gesner under GLO contract number 683 dated June 7, 1898. Surveyor General record states:

Set basalt stone 14x10x4 ins for cor to secs 29,30,31 and 32 from which;

A fir 8 in diam bears N71°E 10 1ks dist A black pine 10 in diam bears S64°E 40 1ks dist A fir 16 in diam bears S55°30'W 27 1ks dist A black pine 14 in diam bears N48°W 27 1ks dist



No record of subsequent remonumentation found in county records Description of corner evidence found:

Stone 14"x9"x4" with grooves visible, also 3/4"x24" iron pipe alongside.

The remains of a Fir bears  $8.55\frac{0}{2}$  W, 27 1ks. Dead and down badly rotted with chop marks visible.

A skid road running East and West 20 feet North of corner, destroyed the Northwest and Northeast bearing trees and the North line tree.

See map of survey number 29-86 filed in the office of the Union County Surveyor

Description of monument and accessories I established to perpetuate the

original location of this corner:At the stone position I set a 2½x30" aluminum pipe with aluminum cap marked as shown 28 inches in the ground and raised a mound of stone with a 2 foot base to top of cap, from which:


A 10 inch Douglas Fir bears N 43° E, 30.88 feet, marked T3S R41E S29 BT.

An 11 inch Tamarack bears S 59° E, 23.45 feet, marked T3S R41E S32 BT.

An 8 inch Tamarack bears S 65° W, 25.57 feet, marked T3S R41E S31 BT.

A 6 inch Tamarack bears N 57° W, 19.10 feet, marked X BT.

Buried Stone East of cap Corner set: 9/5/86 Witness: Rick Robinson



LAND SURVEYOR

REGISTERED

**PROFESSIONAL** 

OREGON JULY 10, 1964

DUANE I. GRIFFITH
644

Brass washer marked OPLS 644 nailed to BT blaze. Used steel tape and magnetic compass with 20° East declination. Distances to the BTs are to a 50d spike set in right side of tree when facing tree, unless otherwise stated.

Office of	····· County of	
State of	, I hereby certify that the within	n instrument was filed in this office
for record on the d	ay of19	<b>r</b> ···
	UNION COUNTY	
(COUNTY OF	SURVEYOR	(DEPUTY)
		ł

Form R6-7100-57 (9/71)

Date Received 10-20-86

Date Filed 10-27-86

BUG LANGUE DEAD

EL N. 773-86 R

☆U,S, GOVERNMENT PRINTING OFFICE - 1983-793-276

V-5

I, 13

## Dependent Resurvey of a Portion of the Subdivisional Lines, T. 3 S., R. 41 E., Willamette Meridian, Oregon

FEET (Restoring the survey by Alonzo Gesner in 1898) From the sec. cor. of secs. 29, 30, 31, and 32, remonumented by Griffith in 1986, recovered and utilized by Griffith in 1988, and by Blackman in 1988; monumented with an aluminum pipe, 2 1/2 ins. diam., firmly set, flush with surface of ground, in a collar of stone, with aluminum cap, 2 1/2 ins. diam., mkd. T 3 S R 41 E 3541 VOE S 30 | S 29 S 31 | S 32 1986 from which the remains of an original bearing tree A dead and down rotted fir log, size indeterminate, bears S. 55 1/2° W., 17.8 ft. dist., no marks visible. and bearing trees mkd. by Griffith A rotted fir stump, 12 ins. diam., bears N. 43° E., 30.6 ft. dist., no marks visible. A tamarack, 17 ins. diam., bears 590 E., UNION COUNTY 23.4 ft. dist., with a healed blaze. SURVEYOR A tamarack. 12 ins. diam., W., 25.6 ft. dist., with a healed blaze. Date Received A tamarack, 11 ins. diam., bears 57° W., Date Filed 19.5 ft. dist., with a healed blaze. a bearing tree mkd. by person(s) unknown A lodgepole pine, 15 ins. diam., bears N. 53° W., 3.1 ft. dist., with a rotted blaze, no scribing visible. and a new bearing tree A fir, 5 ins. diam., bears N. 10 1/2° E., 29.6 ft. dist., mkd. X at breast height and BT at base. at broad the S. 1° 51' 0 "E., bet. secs. 31 and 32. Dirt road, 14 M. wide, bears S. 30° E. and N. 30° W. 1017 The N 1/16 sec. cor of secs. 31 and 32, established by Griffith in 1986, recovered and utilized by Griffith in 1988, and is T3541 1306.50 W05 accepted as 'the corner; monumented with an aluminum pipe, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with aluminum cap, 2 1/2 ins. diam., mkd.