
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by Alonzo Gesner under GLO contract number 683 dated June 7, 1898. Surveyor General record states:

Set basalt stone 15x15x8 ins for cor to secs 28,29,32 and 33 from which;

A black pine 12 in diam bears N7 9 E 11 lks dist A black pine 10 in diam bears S65 $^{\circ}$ 30'E 21 lks dist A black pine 7 in diam bears S47 $^{\circ}$ 30'W 14 lks dist A black pine 12 in diam bears N48 $^{\circ}$ W 8 lks dist



No record of subsequent remonumentation found in county records. Description of corner evidence found:

A stone 15"x15"x8" in a group of 3 large stones.

A Lodgepole Pine bears N 7° E, 11 1ks, dead and down burned with chop marks visible.

Remains of a Lodgepole Pine bears S 4712 W 14 1ks.

A Lodgepole Pine dead and down burned bears $5.65^{+0.0}_{-0.0}$ E, 21 1ks.

A Lodgepole Pine bears N 48° W, 8 lks., dead and down, burned, with chop marks and dim scribing visible.

See map of survey number 29-86 filed in the office of the Union County Surveyor Description of monument and accessories I established to perpetuate the

original location of this corner: At the stone position, I set a 2½ x300 aluminum pipe with aluminum cap marked as shown, 22 inches in the ground and raised a mound of stone with a 3 foot base to top of cap, from which:

A 9 inch Lodgepole Pine bears N 11° E, 47.72 feet, marked T3S R41E S28 BT.

A 7 inch Lodgepole Pine bears S 12° E, 4.68 feet, marked T3S R41E S33 BT.

A 6 inch Lodgepole Pine bears S 31° W, 15.47 feet, marked X BT.

A 7 inch Lodgepole Pine bears N 15° W, 12.30 feet, marked T3S R41E S29BT.

Set a steel fence post approximately 5 feet North with a 54-4 sign attached.

Corner set: 9/3/86

Witness: Greg Blackman, Rick Robinson

GRIFFITH

T3S R41E

S 29 | S 28

S 32 | S 33

Oo 1986 644

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 10, 1964

DUANE I. GRIFFITH

Brass washer marked OPLS 644 nailed to BT blaze. Used steel tape and magnetic compass with 20° East declination. Distances to the BTs are to a 50d spike set in right side of tree when facing tree, unless otherwise stated.

(COUNTY OFFICIAL) SURVEYOR

(DEPUTY)

Form R6-7100-57 (9/71)

Date Received 10.20-86

Date Filed 10-27-86

BY G. LANGUIR DEATY

File No 225-86 R

☆U.S. GOVERNMENT PRINTING OFFICE - 1983-793-276

V**-**9

I-2