

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


X - 17

T 4 N R 38 E

History of original corner establishment:

Corner originally established by Frank W. Campbell under contract # 468 dated April 12, 1883. Set a basalt stone 12"x10"x6", 8" in ground marked 1/4 on West face . from which:

A 10" fir bears S 80° E 12 lks
A 12" fir bears N 85° W 82 lks



In a U.S. Dependent resurvey by Otis O. Gould in August 1939 the stone was found and a 1"x36" iron pipe with a brass cap marked as diagram was set 27" in ground with a mound of stone.
Old BT A 32" fir bears S 65° E 12 lks (7.9 ft.)
Old BT A 30" fir bears S 87 1/2° W 85 lks (56.1 ft.)

Description of corner evidence found:

Found 1" iron pipe with brass cap marked as diagram in a mound of stone. from which:
A 36" fir bears S 65° E 7.9 ft. some marks vis. on chopped out blaze.
A 33" fir bears S 87 1/2° W 56.1 ft Blaze Healed not opened.

Description of monument and accessories | established to perpetuate the original location of this corner:

I drove a steel fence post 3 ft. N.E. of corner and attached a 54.4 sign.

New bearing tree:

A 7" fir bears N 56° W 37.1 feet scribed 1/4 S 34 BT

I nailed an alum. tag to bottom blaze of new tree and painted all blazes red. Painted a red band around all BT's and attached 54-3 and 54-4 signs to them.

I hereby certify the above corner location was perpetuated as herein described in July, 1985

Jud Coppock
Jud Coppock, Witness

UNION COUNTY SURVEYOR
Date Received <u>10-11-85</u>
Date Filed <u>10-14-85</u>
By <u>G. LANGLITZ, DEPUTY</u>
File No. <u>94-85 R</u>

REGISTERED
PROFESSIONAL
LAND SURVEYOR

G. Dennis Edwards

OREGON
JULY 18, 1871
G. DENNIS EDWARDS
951

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....
..... by
(COUNTY OFFICIAL) (DEPUTY)