

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX: L 21


History of original corner establishment:

- A. Corner established by US Deputy Surveyor Frank W. Cambell working under contract numbered 498, dated March 10, 1884.

Surveyor General's Record states:

Set a pine post 3 ft long 3 ins square 24 ins in ground for 1/4 sec cor marked 1/4 S on W face; from which

a pine 10 ins dia brs N72W 25 lks dist marked 1/4S BT
a fir 18 ins dia brs N40E 50 lks dist marked 1/4S BT



UNION COUNTY SURVEYOR

Date Received 10-2-89

Date Filed 10-11-89

By G. LANGLITZ

File No. 194-89R

Description of corner evidence found:

- B. MONUMENT FOUND:


none

ACCESSORIES FOUND:

Found a 21 in dia ponderosa pine N72W at 16.5 feet with healed blaze (did not open).
Found a dead and down fir with visible scribing of "1/4 S BT" at a bearing of N40E at 33.0 feet to center of root collar.

Description of monument and accessories I established to perpetuate the original location of this corner:

- C. I set a 2.5 inch dia. by 30 inch long aluminum monument 24 inches in the ground in a mound of stone. I set the monument at locus of bearing and distance measurements from original bearing trees, as the evidence agrees with the GLO record. I mark the cap:



1989
STRYKER PLS 2060

NEW ACCESSORIES ESTABLISHED with magnetic declination of 20 deg. East
11" ponderosa pine bears N46E at 28.4 ft scribed " 1/4 S13 BT"

Painted red band around each bearing tree
Placed brass washer with "PLS 2060" at base of each new BT blaze
Placed USDA Forest Service metal signs 54-3 (BT) and 54-4 (ATTENTION) on each bearing tree. Placed 54-9 (LSM) sign on steel fence post 1.2 feet north of corner.

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....

(COUNTY OFFICIAL)

(DEPUTY)

Form R6-7100-57 (9/71)

REGISTERED PROFESSIONAL LAND SURVEYOR

Edwin A. Stryker

OREGON
JULY 15, 1983
EDWIN A. STRYKER
2060