


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

N-1

Index File No. ~~7-25~~

History of original corner establishment:

Corner established by Frank W. Campbell under G.L.O. Contract #507 in August, 1884. Surveyor's General's notes state: "Set a post 4 ft. long, 4 ins. square 24 ins. in ground for cor. to Sec. 13, 24, 18 and 19 marked T.4N.S.18 on S.E., R.4OE.S.19 on S.E., R.39E.S.24 on S.W., S.13 on N.W. faces with 3 notches on N. and S. edges, from which: A Spruce 10 ins. dia. brs. N.43°W. 17lks dist. marked T.4N.R.39E.S.13BT.. A Spruce 10 ins. dia. brs. N.15°E. 11lks. dist. marked T.4N.R.4OE.S.18BT.. An Alder 5 ins. dia. brs. S.65°E. 11lks. dist marked T.4N.R.4OE.S.19BT.. A Cottonwood 20 ins. dia. brs. S.28°W. 11lks. dist marked T.4N.R.39E.S.24BT.."



Description of corner evidence found:

No evidence of original corner could be found. A dilligent search was made before the survey and after the corner position was determined.


The Cottonwood thought to be a bearing tree was opened and checked for scribing. No scribing could be found and the tree appears to be too young to fit G.L.O. description.

Corner position is about 15' Southwest of Cottonwood.

Corner is at Northwest edge of Looking Glass Meadow.

Description of monument and accessories I established to perpetuate the original location of this corner:

At single proportionate measurement from found corners, set 2 1/2" x 30" galvanized pipe with brass cap marked: Set pipe 24" in the ground.



No rock in the area.

From which: A Fir 20" in dia. bears N17 1/2°E, 71.1 feet, scribed T4N R4OES18BT. A Cottonwood 26" in dia. bears S34°E, 68.7 feet, scribed T4NR4OES19BT. A Tamarac 12" in dia. bears S88°W, 42.7 feet, scribed T4NR39ES24BT. A Fir 16" in dia. bears N77°W, 43.9 feet, scribed T4NR39ES13BT. Painted blazes red and 6" red band around. Placed 54-3s and 54-4s on BTs. Placed brass washer stamped PLS 1051 on foot blazes. Placed 54-4 on steel fence post 4' East of corner. Placed 54-5 on tree 5' North and on track road 150' West of corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Barry B. Barbour

OREGON
OCT. 17, 1978
BARRY B. BARBOUR
1051

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: David L. Landers
Dan T. Rowland

October 27, 1978

Office of.....County Surveyor..... County of.....Union.....
State of.....Oregon..... I hereby certify that the within instrument was filed in this office
for record on the...20...day of...November....., 19.78

..... by
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY
SURVEYOR
Date Received _____
★ GPO 799-509
Date Filed _____
By _____
File No. 27-83 R