


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

R-1

Index File No. ~~R-25~~

**History of original corner establishment:**

Corner established by Frank W. Campbell under G.L.O. Contract #507 in August, 1884. Surveyor's General's notes state: "Set a post 4 ft. long 4 ins. sqr. 24 ins. in ground for cor. to Sec. 24.25.19 & 30 marked: T.4.N.S19 on N.E., R.40 E.S.30 on S.E., R.39 E.S.25 on S.W. & S.24 on N.W. faces with 4 notches on N. & 2 on S. edges from which: A Spruce 30 ins. dia. brs. N40°W34lks. dist. marked T.4N.R.39E. S.24 B.T.. A Spruce 30ins. dia. brs. N30°S.35lks. dist. marked T.4 N.R.40E. S.19 B.T.. A Spruce 26 ins. dia. brs. S.19 E.38lks dist. marked T.4N.R.40E. S.30BT.. A Fir 10 ins. dia. brs. S.69°W.47lks. dist. marked T.4N.R.39E. S.25B.T.."




**Description of corner evidence found:**

No evidence of original corner could be found. A dilligent search was made before the survey and after the corner position was determined.

Corner falls in a small opening at foot of West slope and about 600' West of new logging road.

**Description of monument and accessories | established to perpetuate the original location of this corner:**

At single proportionate measurement from found corners, set 2 1/2" x 30" galvanized pipe with brass cap marked: Set pipe 24" in the ground.



No rock in the area.

OR PLS 1051  
1978

From which: A Fir 20" in dia. bears N70°E, 50.1 feet, scribed T4NR40ES19BT. A Fir 28" in dia. bears S30°E, 42.4 feet, scribed T4NR40ES30BT. A Fir 30" in dia. bears S86°W, 46.9 feet, scribed T4NR39ES25BT. A Fir 20" in dia. bears N04°W, 48.3 feet, scribed T4NR39ES24BT. Painted blazes red and 6" red band around. Placed 54-3s and 54-4s on BTs. Placed brass washer stamped PLS 1051 on foot blazes. Placed 54-4 on steel fence post 4' North of corner. Placed 54-5 on tree 35' East and on road 600' East of corner.

**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

*Barry B. Barbour*

**OREGON  
OCT. 17, 1975  
BARRY B. BARBOUR  
1051**

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: David L. Landers  
Dan T. Rowland

October 26, 1978

Office of.....County Surveyor..... County of..... Union.....  
State of.....Oregon....., I hereby certify that the within instrument was filed in this office  
for record on the..20.. day of...November....., 1978

..... by .....  
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

**UNION COUNTY  
SURVEYOR**

Date Received \_\_\_\_\_  
☆ GPO 799-509  
Date Filed \_\_\_\_\_  
By \_\_\_\_\_  
File No. 29-83R