Index File No.

History of original corner establishment:

Corner established by Frank W. Campbell under G.L.O. Contract #507 in August, 1884. Surveyor's General's notes state: "Set a post 3 ft. long 3 ins. dia. 24 ins. in ground for 1/4 Sec. corner marked 1/4 S. on W. face, from which: A Spruce 24 ins. dia. brs. S.29 W. 20lks dist. marked 1/4 S.B.T.. A Spruce 24 ins. dia. brs. N.81 E. 39lks dist. marked 1/4 S.B.T..

<u> </u>	LTTE	NO.	7	20		
DIAGRAM						
	R39	T4N E R 1/4	40E	;		
	S25	· + ·	s30			

Description of corner evidence found:

No evidence of original corner could be found. A dilligent search was made before the survey and after the corner position was determined.

A tree was marked by the U.S.F.S. as being a possible BT. It is about 100' Northeast of corner position and possible blaze is in the wrong quadrant. Also a Fir instead of Spruce.

Corner falls in a recently logged area, about 500' North of a road.

Description of monument and accessories I established to perpetuate the

original location of this corner:

At single proportionate measurement from found corners, set 2½" x 30" galvanized pipe with brass cap marked: Set pipe 24" in the ground.

T4N R39E R40E 1/4

No rock in the area.

OR PLS 1051 1978

30-83 R

File No.

From which: A Fir 22" in dia. bears N83°E, 141.4 feet, scribed 1/4S30BT. A Fir 9" in dia. bears N67°W, 79.4 feet, scribed 1/4S25BT. Painted blazes red and 6" red band around. Placed 54-3s and 54-4s on BTs. Placed brass washer stamped PLS 1051 on foot blazes. Placed 54-4 on steel fence post 3' North of corner. Placed 54-5 on tree 5' South of corner and on road 500' South of corner.

REGISTERED **PROFESSIONAL** AND SURVEYOR

OREGON

Form

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses:

David L. Landers Dan T. Rowland

October 26, 1978

Office of County Surveyor co State of Oregon , I hereby certify that t	unty ofUnion	offica
for record on the20. day of November	UNION COUNTY SURVEYOR	
(COUNTY OFFICIAL)	(DEPUTY)	
R6-7100-57 (9/71)		Date Received