CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishments

Corner established in 188 by General Land Office.
(contract survey)
Original survey states: Set a post at the corner
from which;
A spruce 30 in diameter, bears N5 W 9 lks distance
marked \$3BT;
A fir 13 in diameter beras S20 W 15 lks distance
marked \$5BT

J-15
diagram T4n R40EWM
\$10 \$15

Description of corner evidence found:

At recorded distance from the corner I found a 38" fir with the scribe visible at N5°W at a distance of 9 lks. We could not find any trace of other bearing tree. The fir was called a spruce. This tree is very old and for this reason we established two new bearing trees.

Description of monument and accessories I established to perpetuate the original location of this corner

At the position of the corner I placed a galvanized pipe 30" long with a eight inch plate welded to bottom and a bronze cap on top. The pine was set to a depth of 24" and back filled with tamped earth.

t COR I stamped the disk T4N R40E 310 From the pipe monument the original bearing tree is. 315 A fir with scribe at N5°W at a dist. of 9 lks. I also established two new bearing trees: Ore. Lic 381 A fir 20" in diam. bears S69°E at a distance of 1971 24.6 ft. measured to center of the tree and scribed \$SBT: A fir 42" in diam. bears S28°W at a distance of 25.7 ft. measured to center of tree and scribed #SBT;
I placed a treated post by the corner with USFS sign 54-4 attached. USFS bearing tree signs were placed on the three trees breast high and facing the corner.

State of	county of Union vertify that the within instrument was fill 1971, at 8 gicles	led in this effice k & An, (signed)
(COUNTY OFFICIAL)	(DEPUTY)	ORS GON
	UNION COUNTY SURVEYOR	James Cook
Form R6-7100-57 (9/66)	Date Filed	AMIC A TOTAL
Form R6-7100-57 (9/66)	SURVEYOR Date Received	

File No.

37-83 R