


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
Unsurveyed - subdivided section.



Description of corner evidence found:
No evidence found.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the position described above, I set a 2 1/2" x 30" iron pipe 26" in the ground, with a Brass Cap marked as shown:

From which I scribed B.T.'s:

- A Fir 10" in diam. bears N 5°30'E 16.95 feet.
- A Spruce 12" in diam. bears S 64°E 29.90 feet.

I nailed a Brass Washer marked PLS 933 to the B.T. blazes.
I set a steel fence post 5' North and South with signs 54-4, 54-9 & 54-2.
I painted a red band around the B.T.'s and face of scribe, nailed 54-3 & 54-9 signs.
I used a steel tape and a magnetic compass with 19°30' East variation and measured a horizontal distance to the center of B.T.'s.

This corner was set July 21, 1983

By: W. Keith Sands
Witness: Brent Reynolds

REGISTERED
PROFESSIONAL
LAND SURVEYOR

David H. Krumbain

OREGON
JULY 17, 1970
DAVID H. KRUMBEIN
933

T4N R40E
W 1/4 C - C 518
1983
PLS 933

Office of..... County Surveyor..... County of..... Union.....
State of..... Oregon....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....
..... by.....
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY
SURVEYOR

Date Received 9-26-83
Date Filed 9-28-83
By G. LANGLITZ, DEPUTY
File No. 368-83 R

SEE SURVEYS - 37-83
- 38-83